

TYPE: POWDER SPRAY EQUIPMENT TO SPRAY DEVELOPER POWDER
SCOPE OF SUPPLY

a) Integrated 100KV Ininiti™ Manual Corona Gun (U.S. Patent No.5678770)	1 No.
b) Electro pneumatic control panel having Peak Performance Monitor & suitable for Electro & Tribo Guns	1 No.
c) Equipment Trolley Std.	1 No.
d) Stainless Steel Hopper Round- 25Kgs with Pump and inbuilt stirrer unit	1 No.
e) Complete set of Nozzles, Cables, and Hoses & Accessories for start up.	1 Set.

PNEUMATIC DATA

Maximum input pressure	10 bar
Optimum input pressure	6 bar
Maximum water vapour content in compressed air	1.3 g/Nm ³
Maximum oil vapour content in compressed air	0.1 ppm
Maximum Compressed air consumption	13.2m ³ /hr

ELECTRICAL DATA

Single phase AC current, selectable voltages	220V or 230/110V
Frequency	50 / 60 Hz.
Connected loads	65VA
Safety class	IP 54 (P43)
Temperature Range	+2 °C to 50 °C
Nominal Input Voltage	10 V eff.
Output Voltage	100 KVDC -ve (+ve on request)
Nominal Output Current	100 micro amps.